
FRANCE

P & PC SERIES

**Models for Export Only
Outdoor Non-weatherproof**



- ◆ Heavy Duty Steel Casing
- ◆ Secondary Balanced Mid-point Ground Units Provide Versatility in Wiring Methods - Virtual Series, Mid-point Return or Series
- ◆ Recommended for Remote Installations
- ◆ PC Series Requires Less Input Current Maximizing Capacity of a 20 Amp Circuit

www.franceformer.com

2268 Fairview Blvd PO Box 300 Fairview, TN 37062 voice 800-753-2753 fax 615-799-3199

P & PC SERIES

NORMAL POWER FACTOR

Catalog Number	Secondary		Primary VA	Input Amp	Wt lbs	Dimensions in Inches					
	Volts	mA				L	W	H	A	B	C
* ♦ 15030 P	15000	30	450	3.75	24	14.13	4.188	5.188	9.25	3	10.13
* ♦ 12030 P	12000	30	360	3.00	21	14.13	3.813	5.188	9.25	1.88	10.13
* ♦ 10530 P	10500	30	315	2.63	21	14.13	3.813	5.188	9.25	1.88	10.13
* 9030 P	9000	30	270	2.25	16	12.88	3.813	3.88	9.25	1.88	10.13
* ♦ 15060 P	15000	60	890	7.72	41	15.688	5.375	6.188	10.813	3	11.875
* ♦ 12060 P	12000	60	720	6.00	38	15.688	5.375	6.188	10.813	3	11.875
* ♦ 9060 P	9000	60	540	4.50	27	14.13	4.688	5.188	9.25	3	10.13
* ♦ 7560 P	7500	60	450	3.75	22	14.13	4.188	5.188	9.25	3	10.13
* ♦ 6060 P	6000	60	360	3.00	21	14.13	3.813	5.188	9.25	1.88	10.13
* ♦ 5060 P	5000	60	300	2.50	20	14.13	3.813	5.188	9.25	1.88	10.13
* ♦ 4060 P	4000	60	240	2.00	14	14.13	3.813	3.88	9.25	1.88	10.13

♦ Model available in 277 VAC/60 Hz. To determine Input Amps multiply by 0.433.

* Secondary - Balanced Mid-point Ground

♦ Secondary - Unbalanced Mid-point Ground

HIGH POWER FACTOR

Catalog Number	Secondary		Primary VA	Input Amp	Wt lbs	Dimensions in Inches					
	Volts	mA				L	W	H	A	B	C
* ♦ 15030 PC	15000	30	250	2.08	24	14.13	4.688	5.188	9.25	3	10.13
* ♦ 12030 PC	12000	30	200	1.67	25	14.13	4.688	5.188	9.25	3	10.13
* ♦ 10530 PC	10500	30	175	1.46	24	14.13	4.188	5.188	9.25	3	10.13
* 9030 PC	9000	30	150	1.25	20	14.13	3.813	5.188	9.25	1.88	10.13
* 7530 PC	7500	30	125	1.04	14	14.13	3.813	3.88	9.25	1.88	10.13
* ♦ 6030 PC	6000	30	100	0.83	13	14.13	3.813	3.88	9.25	1.88	10.13
* ♦ 5030 PC	5000	30	90	0.75	10	14.13	3.813	3.88	9.25	1.88	10.13
* ♦ 4030 PC	4000	30	75	0.63	10	14.13	3.813	3.88	9.25	1.88	10.13
* ♦ 15060 PC	15000	60	495	4.13	44	15.688	5.375	6.188	10.813	3	11.875
* ♦ 12060 PC	12000	60	400	3.33	41	15.688	5.375	6.188	10.813	3	11.875
* 9060 PC	9000	60	300	2.50	27	14.13	4.688	5.188	9.25	3	10.13
* 7560 PC	7500	60	250	2.08	24	14.13	4.688	5.188	9.25	3	10.13
* 6060 PC	6000	60	200	1.67	24	14.13	4.688	5.188	9.25	3	10.13
* 5060 PC	5000	60	170	1.42	20	14.13	4.688	5.188	9.25	3	10.13
* ♦ 4060 PC	4000	60	135	1.12	14	14.13	3.813	3.88	9.25	1.88	10.13

♦ Model available in 277 VAC/60 Hz. To determine Input Amps multiply by 0.433.

* Secondary - Balanced Mid-point Ground

♦ Secondary - Unbalanced Mid-point Ground

