When it has to work... EVERY TIME. Count on **Atlas Power Supplies.**

Featuring an LED Status Indicator that instantly alerts you of an overload or short.



WET-LISTED 60W 12V CLASS 2 LED POWER SUPPLY



No power de-rating required

Supports 100% 60W load across the entire operating temperature range. Light more LEDs with less power supplies, creating cost savings.

High electrical efficiency

Enables low energy costs and cool operation in a small package. Features an 85°C maximum case temperature.

\land

Maximum water resistance

IP68 rating and wet-listed conduit fittings. For use in wet, dry or damp applications.



For more information, contact your France distributor or email us at sales@sfeg.com



Atlas Power Supply DRV-1260-A Specifications







Size

8.7" Long x 1.97" Wide x 1.42" Tall Including Baseplate & Conduit Fittings, 2 lbs.

Ambient Operating Temperature

-30°C to 60°C

Input

120/277VAC, 50/60Hz, 1.2/.70 Amp Max

Output

12VDC, 5 Amp, 60 Watt Class 2 No Minimum Loading Requirement

Lead Length

12" RTJW Input and Output Environment

IP68, for use in dry, damp, or wet locations UL Listed Class P Type HL, suitable for hazardous locations FCC 47 CFR 15 Subpart B Residential or Commercial use.

Warranties

5 Year France LED Parts Warranty

1 Year Labor Warranty



For more information, contact your France distributor or email us at sales@sfeg.com