

FRANCE

LIGHTING SOLUTIONS

FFG-7



Indoor Window Frame Transformer

ADVANTAGES

UL 2161 Listed

Easy Frame Mounting on indoor window type neon signs of virtually any size or style

8 foot three-conductor line cord with three prong plug, plus-chain on/off switch, and 24" long secondary cable

Secondary Circuit Ground Fault Protection

Models 9030 and 7530 are disabled upon detection of arcs to ground in compliance with UL2161, C22.2 No. 255 and NEC requirements.

MODELS

9030 FFG-7

Secondary Output: 9kV, 30mA

Model Number: 68168

7530 FFG-7

Secondary Output: 7.5kV, 30mA

Model Number: 68234

6030 FFG-7

Secondary Output: 6kV, 30mA

Model Number: 68232

5030 FFG-7

Secondary Output: 5kV, 30mA

Model Number: 68230

4030 FFG-7

Secondary Output: 4kV, 30mA

Model Number: 68228

NORMAL POWER FACTOR

Catalog Number	VAC	Hz	Secondary		Primary VA	Input Amps	Weight (lbs)	Case Dimensions (inches)			
			Volts	mA				L	W	H	A
9030 FFG-7	120	60	9000	30	300	2.50	10	8.16	3.72	3.25	2.63
7530 FFG-7	120	60	7500	30	260	2.10	9	8.16	3.72	3.25	2.63
6030 FFG-7	120	60	6000	30	200	1.65	9	8.16	3.72	2.86	2.23
5030 FFG-7	120	60	5000	30	170	1.40	9	8.16	3.72	2.86	2.23
4030 FFG-7	120	60	4000	30	140	1.15	9	8.16	3.72	2.86	2.23

