



Indoor/Outdoor Non-weatherproof Internal Mount Electrode Housing

ADVANTAGES

UL 2161 Recognized component

Pre-wired Primary

Heavy duty steel construction

FRANCE

LIGHTING SOLUTIONS

PBKMG-51

60W, 120V



MODELS

9060 PBKMG-51

Secondary Output: 9kV, 60mA

Model Number: 68369

7560 PBKMG-51

Secondary Output: 7.5kV, 60mA

Model Number: 68371

6060 PBKMG-51

Secondary Output: 6kV, 60mA

Model Number: 68043

5060 PBKMG-51

Secondary Output: 5kV, 60mA

Model Number: 68037

4060 PBKMG-51

Secondary Output: 4kV, 60mA

Model Number: 68029

3060 PBKMG-51

Secondary Output: 3kV, 60mA

Model Number: 68026

NORMAL POWER FACTOR																
Catalog Number	VAC	Hz	Secondary		Primary VA	Input Amps	Secondary Ground*	Weight (lbs)	Case Dimensions (inches)							
			Volts	mA					L	W	H	A	B	C	D	E
9060 PBKMG-51	120	60	9000	60	540	4.50	BMPG	21	15.125	3.766	3.447	13.625	14.250	2.0	1.8	1.3
7560 PBKMG-51	120	60	7500	60	450	3.75	BMPG	21	15.125	3.766	3.447	13.625	14.250	2.0	1.8	1.3
6060 PBKMG-51	120	60	6000	60	360	3.00	BMPG	15	11.875	3.766	3.080	10.375	11.00	2.0	1.8	1.3
5060 PBKMG-51	120	60	5000	60	300	2.50	BMPG	15	11.875	3.766	3.080	10.375	11.00	2.0	1.8	1.3
4060 PBKMG-51	120	60	4000	60	240	2.00	UMPG	11	10.125	3.766	3.080	8.625	9.250	2.0	1.8	1.3
3060 PBKMG-51	120	60	3000	60	180	1.50	UMPG	11	10.125	3.766	3.080	8.625	9.250	2.0	1.8	1.3

*Secondary Ground:

BMPG = Balance Mid-Point Ground

UMPG = Unbalanced Mid-point Ground

OEG = One End Ground

