



Indoor/Outdoor Non-weatherproof Internal Mount Electrode Housing

ADVANTAGES

UL 2161 Recognized component

Pre-wired Primary

Heavy duty steel construction

FRANCE

LIGHTING SOLUTIONS

PBKMG-51

60W, 277V



MODELS

9060 PBKMG-51 277

Secondary Output: 9kV, 60mA

Model Number: 68370

7560 PBKMG-51 277

Secondary Output: 7.5kV, 60mA

Model Number: 68372

6060 PBKMG-51 277

Secondary Output: 6kV, 60mA

Model Number: 68044

5060 PBKMG-51 277

Secondary Output: 5kV, 60mA

Model Number: 68038

4060 PBKMG-51 277

Secondary Output: 4kV, 60mA

Model Number: 68030

NORMAL POWER FACTOR																
Catalog Number	VAC	Hz	Secondary		Primary VA	Input Amps	Secondary Ground*	Weight (lbs)	Case Dimensions (inches)							
			Volts	mA					L	W	H	A	B	C	D	E
9060 PBKMG-51 277	277	60	9000	60	540	1.95	BMPG	21	15.125	3.766	3.447	13.625	14.250	2.5	1.8	1.5
7560 PBKMG-51 277	277	60	7500	60	420	1.63	BMPG	21	15.125	3.766	3.447	13.625	14.250	2.5	1.8	1.5
6060 PBKMG-51 277	277	60	6000	60	370	1.34	BMPG	15	11.875	3.766	3.080	10.375	11.000	2.0	1.8	1.3
5060 PBKMG-51 277	277	60	5000	60	300	1.08	BMPG	15	11.875	3.766	3.080	10.375	11.000	2.0	1.8	1.3
4060 PBKMG-51 277	277	60	4000	60	240	.87	UMPG	11	10.125	3.766	3.080	8.625	9.250	2.0	1.8	1.3

*Secondary Ground:
 BMPG = Balance Mid-Point Ground
 UMPG = Unbalanced Mid-point Ground
 OEG = One End Ground

